


REFINE[®]

A SPRAY GUN REFINED OVER 45YS TECHNOLOGY



Precise holing

Sanding chromed



RS8806

PROFESSIONAL HIGH-EFFICIENT PRIMER SPRAY GUN

- German atomization engineering and quality standard.
- Unified fine atomization and wet core are ensuring excellent coverage of paint and leveling thus increasing spray efficiency.
- High quality stainless nozzles tip, needle, air cap and springs are processed state-of-the-art Five-axis CNC technologies ensuring precision and longevity.
- Ergonomic design and non-stick matt chromed finishing create user-friendly hand feeling and easy cleaning.
- The cup is made of POM materials; and all gaskets are solvent-resistant PTFE materials.
- Streamlined body design makes it more cost-effective and lightweighted while sustaining quality and performance.



TECHNICAL DATA

Model	RS8806GR
Atomization technology	LVMP
Recommended spray pressure	0.5-2.5bar
Optimum spray pressure	2.0-2.5bar
Standard nozzle size	1.3/1.7mm
Spraying distance	17-21CM
Air consumption	250L/min
Pattern length	230-250mm
Paint cup size	600ml
Transfer rate	≥60%
Atomized particle	30-50um
Package:10pcs/68*34*24.5cm, NW/GW:9.5/10.5KGS	

LVMP

